



7211 BECBY Bearing 2D drawings and 3D CAD models

55 mm x 100 mm x 21 mm skf 7211 BECBY  
Single row angular contact ball bearings

Bearing No. 7211 BECBY

Size	100x55x21 mm
Bore Diameter	100 mm
Outer Diameter	55 mm
Width	21 mm
d	55 mm
D	100 mm
B	21 mm
d <sub>1</sub>	72.45 mm
d <sub>2</sub>	63.62 mm
D <sub>1</sub>	83.7 mm
a	43 mm
r <sub>1,2</sub> - min.	1.5 mm
r <sub>3,4</sub> - min.	1 mm
d <sub>a</sub> - min.	64 mm
D <sub>a</sub> - max.	91 mm
D <sub>b</sub> - max.	94 mm
r <sub>a</sub> - max.	1.5 mm
r <sub>b</sub> - max.	1 mm
Basic dynamic load rating - C	48.8 kN
Basic static load rating - C <sub>0</sub>	38 kN
Fatigue load limit - P <sub>u</sub>	1.6 kN
Reference speed	7500 r/min
Limiting speed	7500 r/min
Calculation factor - k <sub>r</sub>	0.095



## ACW BEARING EXPORTED LTD

Calculation factor - $k_a$	1.4
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - $Y_0$	0.52
Calculation factor - $Y_1$	0.55
Calculation factor - $Y_2$	0.93
Calculation factor - X	0.35
Calculation factor - $Y_0$	0.26
Calculation factor - $Y_1$	
Calculation factor - $Y_2$	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.62
EAN	7316576649981
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric



## ACW BEARING EXPORTED LTD

Long Description	55MM Bore; 100MM Outside Diameter; 21MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7211 BECBY
Weight / LBS	1.358
Bore	2.165 Inch   55 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
Width	0.827 Inch   21 Millimeter
bore diameter:	55 mm
radial static load capacity:	38 kN
outside diameter:	100 mm
cage material:	Brass
overall width:	21 mm
outer ring width:	21 mm
contact angle:	40 °
maximum rpm:	7500 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	1.5 mm

## ACW BEARING EXPORTED LTD

radial dynamic load capacity:	48.8 kN
series:	72
$d_1$	72.45 mm
$d_2$	63.62 mm
$D_1$	83.3 mm
$r_{1,2}$ min.	1.5 mm
$r_{3,4}$ min.	1 mm
$d_a$ min.	64 mm
$D_a$ max.	91 mm
$D_b$ max.	94 mm
$r_a$ max.	1.5 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	51 kN
Basic static load rating $C_0$	42.5 kN
Fatigue load limit $P_u$	1.8 kN
Calculation factor A	0.0235
Calculation factor $k_r$	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	0.62 kg