


38,1 mm x 73,025 mm x 25,654 mm NTN
4T-2788/2735X Single row tapered roller bearings



Bearing No. 4T-2788/2735X

4T-2788/2735X Bearing 2D drawings and 3D CAD models

Size	38.1x73.025x23.812 mm
Bore Diameter	38,1 mm
Outer Diameter	73,025 mm
Width	23,812 mm
d	38,1 mm
D	73,025 mm
T	23,812 mm
B	25,654 mm
C	19,05 mm
a	16 mm
rs min	3.56 mm
r1s min	0.8 mm
e	0.3
Y2	1.98
Y0	1.09
Mass	0.44 kg
Dynamic load, C	73 kN
Rating life coefficient, A2	1.4
Static load, C0	90.5 kN
Nlim (oil)	6,800 rpm
Nlim (grease)	5,100 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.42 Hz



ACW BEARING EXPORTED LTD

frequency, FTF	
Characteristic rolling element frequency, BSF	6.34 Hz
Characteristic outer ring frequency, BPF0	7.22 Hz
Characteristic inner ring frequency, BPF1	9.78 Hz
ra max	3.5 mm
r1a max	0.8 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.444
Product Group	B04334